

**Description:**

Upshur Collection 52 in. Brushed Nickel Transitional Ceiling Fan with LED Light Kit  
 52" Fan

**Specifications:**

- Frosted White Acrylic Round
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" recessed outlet box: 6.31 in W., 2.06 in ht., 6.31 in depth
- Mounting Bracket
- 80 in of wire supplied

**Performance:**

Number of Modules	1
Input Power	18 W
Input Voltage	120/277 VAC
Input Frequency	60 Hz
Lumens/LPW (Delivered)	1,450/80.56 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	54000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Warranty	Limited Lifetime Warranty
Labels	ETL Damp Location Listed Meets California Title 24 JA8-2019 AC motor

**P250094-009-30**



**Dimensions:**

Diameter: 52 in  
 Height: 13-11/16 in

Frosted White Acrylic Round  
 Width: 6-7/8 in  
 Height: 1-15/16 in

<b>ENERGYGUIDE</b>	
<p>Estimated Yearly Energy Cost</p> <p><b>\$9.0</b></p> <p>\$3       \$34</p> <p>Cost Range of Similar Models (19" – 84")</p> <p>• Based on 12 cents per kWh and 6.4 hours use per day          • Your cost depends on rates and use          • Energy Use: 34 Watts</p>	<p>Airflow</p> <p><b>3,408</b></p> <p>Cubic Feet Per Minute</p> <p>• The higher the airflow, the more air the fan will move          • Airflow Efficiency: 102 Cubic Feet Per Minute Per Watt</p>
<p>All estimates based on typical use, excluding lights</p>	
<p><a href="http://ftc.gov/energy">ftc.gov/energy</a></p>	

**Photometrics:**

---

<b>ELECTRICAL DATA</b>	<b>P250094-009-30</b>
Input Voltage	120/277 VAC
Input Frequency	60 Hz
THD	<20%
EMI/RFI	FCC Title 47, Part 15, Class B
Dimming	Yes*
Over-voltage, over-current, short-circuit protected	
*See Dimming Notes for more information	

**P250094-009-30**